



Specification			Condition
L Pri (P3-P4)	12.0uH +/-15%		1.0kHz
L Sec (P1-P2)	295mH +/-15%		
DCR Pri (P3-P4)	128m?		Max
DCR Sec	1400?		Max
Withstand Voltage	3kV		
Ratio	1:18		
Operating Temp	-30 to +120 Deg C		
Breakdown	7kV/mm min		
Materials	Material	UL File	
Bobbin	PBT-4130	E59481	Chang Chun Plastics
Core	Ferrite H6L16x15		Ho-Yu Electronics
Wire	TY1700- U155	E84201	Ta Ya Electric
Epoxy	5002A & 5002B		Flying Dragons
Flammability	UL94V-0		
Marking	INV98038 + Production Code ww-yy		

**Proprietary and Confidential**  
The information contained in this drawing is the sole property of AIC Technology (Europe) Ltd. Any reproduction in whole or part without the written permission of AIC Technology (Europe) Ltd is strictly prohibited

AIC Technology (Europe) Ltd.			
<a href="http://www.aiceurope.com">www.aiceurope.com</a>			
Drawn	dw	Title INV98038	
Checked	th		
Customer Part No		N/A	
Unless otherwise specified dimensions are in millimetres		Issue	Rev
Do Not Scale Drawing		A	00